



To meet the growing need for crisp, sleek, uncluttered rain water pipes for use on more contemporary buildings without going to the expense of a fully secret fixed system such as Flush Fix shown on page 16. Guttermaster has developed this new range Minimalist,

Standard Pipe Length

CIRCULAR PIPE:

dim (mm) Ref: MIN/63 MIN/75 MIN/100 MIN/150

W	63.5	76	102	150
T	1.6	1.6	1.6	2.5
L	TO 6,000	TO 6,000	TO 6,000	TO 6,000




Evans Offset 2 Part Adjustment

dim (mm) Ref: MIN/3x3 MIN/4x3

P	TO 3,000	TO 3,000
L	100	

dim (mm) Ref: MIN/4x4

P	TO 3,000	TO 3,000
L	100	100



Available in standard 92.5, 112.5 and 135 degree, other angles available

Plinth Offset


To bring flush-fix pipe away from wall to permit connection to drain.

dim (mm) Ref: MINPO/3x3 INPO/4x3

P	TO 150	TO 150
L	100	100

dim (mm) Ref: MINPO/4x4 MINPO/6x6

P	TO 150	TO 150
L	100	100



Available in standard 135 degree, other angles available


Access Pipe/Rodding Eye

dim (mm) Ref: MINAP/3x3 MINAP/4x3

L	300	300
---	-----	-----

dim (mm) Ref: MINAP/4x4 MINAP/6x6

L	300	300
---	-----	-----



Bend

dim (mm) Ref: MINBE/3x3 MINBE/4x3

L	100	100
---	-----	-----

dim (mm) Ref: MINBE/4x4 MINBE/6x6

L	100	100
---	-----	-----

Available in standard 92.5, 112.5 and 135 degree, other angles available.
Bend to right indicated, other orientations available.



Shoe

dim (mm) Ref: MINSH/3x3 MINSH/4x3

L1	100	100
----	-----	-----

L2	40	40
----	----	----

dim (mm) Ref: MINSH/4x4 MINSH/6x6

L1	100	100
----	-----	-----

L2	40	40
----	----	----



Special Features:

- Loose smooth male female sockets
- Long lengths of powder coated rainwater pipes can be supplied (up to 6m)
- 3 fixing types available as standard
 - Saddle clips simple one piece economical
 - Small 'T' base clip unobtrusive and suitable for recesses
 - Extension base clips site adjustable for variable projections
- Unlimited hopper heads available

Standard Hopper Heads


dim (mm) Ref: DIHH/63 DIHH/75 DIHH/100

W	257	257	257
---	-----	-----	-----

D	179	179	179
---	-----	-----	-----

H	175	175	175
---	-----	-----	-----

Many other types of Hopper Heads are readily available - Please enquire.



Rectangular Hopper Head


dim (mm) Ref: HH002/63 HH002/75 HH002/100 HH002/150

W	400	400	400	400
---	-----	-----	-----	-----

D	200	200	200	200
---	-----	-----	-----	-----

H	300	300	300	300
---	-----	-----	-----	-----

Or sized to suit requirements.



Small Base Clip

For use when pipe is positioned in narrow recesses.

CIRCULAR:

dim (mm) Ref: DIBC/63 DIBC/75


C	31	31
---	----	----

W	92	98
---	----	----

dim (mm) Ref: DIBC/100 DIBC/150

C	31	31
---	----	----

W	111	136
---	-----	-----



Saddle Clip

For use as intermediate fixing when using eared sockets.

CIRCULAR:

dim (mm) Ref: DISC/63 DISC/75


C	80	110
---	----	-----

W	56	70
---	----	----

dim (mm) Ref: DISC/100 DISC/150

C	110	168
---	-----	-----

W	91	116
---	----	-----



Extension Base Clip - Adjustable

For use when pipe requires fixing up to 250mm from structure.

CIRCULAR:

dim (mm) Ref: DIEB/63 DIEB/75


C	45	45
---	----	----

W (max)	282	288
---------	-----	-----

dim (mm) Ref: DIEB/100 DIEB/150

C	45	45
---	----	----

W (max)	301	326
---------	-----	-----



TO GUTTER OUTLET

TO DRAIN